

Installing Dish 1000 with Super Buddy™ meter



Connections: LNBS: DPP (110° and 119°) and DP (129°). Connect the DPP to the Super Buddy.

Meter Setup:

Push the **SYST** System soft-key to select the following:

- REGION your geographic region
- SERVICE **Dish Network**
- SYSTEM **Dish 1000**
- LNB MODEL **Dish 1000**
- SWITCH TYPE defaults to **DP Plus or DP 34**

To make selections, arrow to the entry to change and press **Enter**, then arrow to the desired option and press **Enter**. Press **EXIT** or **DONE** to return to Run Mode

Run Mode:

Use the **LNB** soft-key to power the LNB and to toggle between satellites.

LNB 1 = 119° (orbital slot will be noted in upper left corner of display)

LNB 2 = 110°

LNB 3 = 129°

NOTE: For multi-LNB systems we recommend you use the **LNB** button to select different satellites rather than the left/right arrows.

After pressing the **LNB** soft-key to power the LNB and select the satellite:

- Align the antenna to obtain a strong signal level and LOCK.
- Press the **ID** soft key to verify the satellite. "ID VERIFIED" means you are pointed correctly.
- If ID fails, press **SCAN** soft-key and Super Buddy will find the satellite you are aimed at.
- Use Up/Down arrows to scroll through transponders to check for proper level and quality.



Application Note

10/27/2006

Applied Instruments, Inc. • 5230 Elmwood Ave. • Indianapolis, IN USA 46203 • T (317) 782-4331 • www.appliedin.com