



## Application Note

02/07/2009

### Installing StarBand/Spacenet with Super Buddy™ satellite meter

**Connections:** Connect LNB to top (SIGNAL IN) port of Super Buddy meter with coax cable.

#### Meter set-up

Press the **SYST** System soft-key (located near top left corner of LCD screen) to enter the System Setup menu. Then select the following:

- REGION                    your geographic region
- SERVICE                   **Other Providers**
- SYSTEM                   **Star Band**
- LNB MODEL               **(N/A)**
- SWITCH TYPE             defaults to **none**

*To make selections, press up/down arrow keys to scroll to the item to change and press **Enter**. Press **EXIT** or **DONE** to return to Run Mode*

#### Antenna Pointing

Install the mast plumb, preset the antenna vertical angle, mount to mast and grossly align azimuth. You may want to use the ZIP code look-up table to obtain rough antenna settings.

- Press the left / right arrow keys to select the desired satellite (orbital position displayed in upper left corner of LCD screen). Refer to your StarBand/Spacenet paperwork to know which satellite to aim dish at.
- Press the **ZIP** zip code soft-key, type in the local zip code using the numeric keypad, and press **ENTER**. Approximate antenna settings will be displayed. Press **EXIT** soft-key to return to the main Run screen.

#### Run Mode

- Press the soft-key in the upper right corner of the LCD screen to choose the correct receive polarity, selecting either horizontal (**HZ**) or vertical (**VT**) receive polarity. Refer to your StarBand/Spacenet paperwork to know which receive polarity to use.
- Press **LNB** soft-key (located on middle right side of LCD screen) to power the LNB.

After selecting the satellite, receive polarity and pressing the **LNB** soft-key to power the LNB:

- Adjust the antenna azimuth and elevation to obtain maximum signal level (left bar graph), signal quality (right bar graph), and LOCK status.
- Rotate the LNB and feed horn assembly (adjusting the polarity offset) to maximize signal level and quality.
- Press the **ID** soft-key to verify the satellite. "ID VERIFIED" means you are pointed correctly.
- If "ID FAILED" is displayed, press **SCAN** soft-key and Super Buddy will find which satellite you are aimed at.
- If desired, you may also use Up/Down arrow keys to scroll through other transponders to check for proper signal level and quality.

#### Other Notes:

-It is NOT recommended to keep Super Buddy meter in line while checking modem status due to attenuation from our circuitry.